



The McCloskey 616 trommel screener combines high production rates and ease of use in a cost effective machine. Ideal for sand and gravel, recycling, composting, or other large bulk material handling applications, this portable screening plant processes large amounts of material without spillage or build-up at the transfer points. Raise and lower the patented 180° radial stacking conveyor to feed into a stacker or directly into trucks. Now available with track mobility.

Features, Benefits, and Options

- *New for 2005* – Rubber drum extension and track mobility
- Five lifting bars on drum provide aggressive screening action
- Patented remote controlled 180° radial stockpiling conveyor with a variable discharge height for maximum stockpiling results
- Drum exchange system for maximum versatility
- End conveyor for efficient stockpiling of oversized material
- Remote controlled hydraulic tipping grizzly or vibrating grizzly
- Quick and easy set up and tear down with no tools required
- All belts and drum feature reversible operation



Specifications (616 with radial and end conveyor and tracks)

Engine:	127 HP (95 kw) Caterpillar diesel engine
Hopper:	13 ft.. 6 in. x 6 ft. (3.8 m x 1.83 m)
Screen:	6 ft. diameter x 16 ft. long (1.8 m x 4.9 m)
Weight:	50,780 lbs (23,033 kgs)
Transport Height :	13 ft. 6 in. (4.1 m)
Transport Length:	52 ft. 5.125 in. (17.42 m)
Transport Width:	7 ft. 8.5 in. (2.35 m)

Specifications vary with screener options and are subject to change without notice.

Canada and United States:

1-877-TROMMEL

International: 001-705-295-4925

UK Office: +44 28 8774 0926